

# MicroCAT C-T (P optional) Sensor (Serial Interface)

**SBE 37-SI**  


## SUMMARY

- Conductivity, Temperature, and (optional) Pressure, at user-programmable intervals (1 second to 6 hours).
- RS-232 serial interface (RS-485 optional), internal memory, and external power.
- Expendable anti-foulant devices for bio-fouling protection.
- Depths to 350 meters (*ShallowCAT* plastic housing) or 7000 meters (titanium housing).
- Sea-Bird's field-proven MicroCAT family, with more than 8000 instruments deployed since 1997.

## DESCRIPTION

The SBE 37-SI MicroCAT is a high-accuracy conductivity and temperature (pressure optional) sensor with **Serial Interface**, which includes a non-volatile FLASH memory. Externally powered, it is useful as a stand-alone monitoring device, and is easily integrated with current meters, ROVs, AUVs, towed sonars, and other instrumentation platforms. Constructed of titanium and other non-corroding materials to ensure long life with minimum maintenance, the MicroCAT's depth capability is 7000 meters; it is also available with an optional 350-meter plastic *ShallowCAT* housing.

Calibration coefficients are stored in EEPROM, allowing the MicroCAT to output data in ASCII engineering units (decimal or XML format); raw output is also available. Data always includes Conductivity, Temperature, and (optional) Pressure; users can choose to add any combination of time, sound velocity (Chen-Millero), salinity, depth, and density.

## SENSORS AND SENSOR INTERFACE ELECTRONICS

The MicroCAT retains the temperature and conductivity sensors used in our time-proven SeaCAT and SeaCAT *plus* products. Electrical isolation of the conductivity electronics eliminates any possibility of ground-loop noise. The MicroCAT's unique internal-field conductivity cell permits the use of expendable anti-foulant devices. Its aged and pressure-protected thermistor has a long history of exceptional accuracy and stability.

The optional strain-gauge pressure sensor is available in eight ranges, from 0 - 20 meters to 0 - 7000 meters. Compensation of the temperature influence on pressure offset and scale is performed by the MicroCAT's CPU.

Temperature is acquired by applying an AC excitation to a hermetically-sealed VISHAY reference resistor and an ultra-stable aged thermistor (drift rate typically less than 0.002 °C per year). The ratio of thermistor resistance to reference resistance is determined by a 24-bit A/D converter; this A/D also processes the pressure sensor signal. Conductivity is acquired using an ultra-precision Wien-Bridge oscillator.

## COMMUNICATIONS AND INTERFACING

The MicroCAT communicates via standard RS-232 serial interface. Real-time data can be transmitted up to 1600 meters (5200 feet) at 600 baud (power considerations may limit distance), simultaneous with recording. Data can be uploaded at up to 115.2K baud. Firmware upgrades can be downloaded through the communications port, without opening the instrument. An optional RS-485 interface allows multiple MicroCATs to share a common 4-wire cable (power, common, data +, data -), minimizing cable complexity for C-T chains.

User-selectable operating modes include:

- **Autonomous Sampling** — The MicroCAT is pre-programmed to sample, store data in FLASH memory, and transmit data. There are two types of autonomous sampling:
  - *Continuous sampling* at the fastest rate possible (1.0 second minimum without pressure).
  - *Interval sampling* at intervals of 6 seconds to 6 hours.
- **Polled Sampling** — On command from a computer or satellite, radio, or wire telemetry equipment, the MicroCAT wakes up, samples, and transmits data.
- **Serial Line Sync** — In response to a pulse on the serial line, the MicroCAT wakes up, samples, stores data in FLASH memory, transmits data, and goes to sleep.

## SOFTWARE

The MicroCAT is supplied with a powerful Windows 2000/XP software package, Seasoft® V2, which includes:

- SeatermV2® – terminal program for easy communication and data retrieval.
- SBE Data Processing® – programs for calculation, display, and plotting of conductivity, temperature, pressure (optional), and derived variables such as salinity and sound velocity.



**Sea-Bird Electronics, Inc.**

13431 NE 20th Street, Bellevue, Washington 98005 USA  
Website: [www.seabird.com](http://www.seabird.com)

E-mail: [seabird@seabird.com](mailto:seabird@seabird.com)  
Telephone: +1 425-643-9866  
Fax: +1 425-643-9954

## SPECIFICATIONS

### Measurement Range

Conductivity: 0 - 7 S/m (0 - 70 mS/cm)  
 Temperature: -5 to 35 °C  
 Optional Pressure: 20/100/350/600/1000/2000/3500/7000  
 (meters of deployment depth capability)

### Initial Accuracy

Conductivity: ± 0.0003 S/m (0.003 mS/cm)  
 Temperature: ± 0.002 °C  
 Optional Pressure: ± 0.1% of full scale range

### Typical Stability

Conductivity: 0.0003 S/m (0.003 mS/cm) per month  
 Temperature: 0.0002 °C per month  
 Optional Pressure: 0.05% of full scale range per year

### Resolution

Conductivity: 0.00001 S/m (0.0001 mS/cm)  
 Temperature: 0.0001 °C  
 Optional Pressure: 0.002% of full scale range

### Clock Stability

5 seconds/month

### Memory

8 Mbyte; capacity in excess of 530,000 samples

### Input Power

0.5 Amps at 8.5 - 24 VDC

### Quiescent Current\*

30 microAmps

### Communication Current\*

4.3 milliAmps

### Acquisition Current\*

15 milliAmps

### Acquisition Time

1.0 - 2.6 seconds/sample, dependent on sampling mode and inclusion of pressure sensor

### Housing, Depth Rating, & Weight (without pressure or clamps)

**Standard**  
 Titanium, 7000 m (23,000 ft)  
 Weight in air: 2.9 kg (6.5 lbs)  
 Weight in water: 1.9 kg (4.3 lbs)

**Optional ShallowCAT**  
 Plastic, 350 m (1150 ft)  
 Weight in air: 2.2 kg (4.9 lbs)  
 Weight in water: 1.2 kg (2.7 lbs)

\* Power consumption values are for standard RS-232 interface; for optional RS-485 interface, see RS-485 manual.

