

C3 Submersible Fluorometer



C3 Submersible Fluorometer

The C3 Submersible Fluorometer can be configured with one, two or three optical sensors ranging from the deep ultraviolet to the infrared spectrum. Internal memory storage capacity combined with an external submersible lithium ion battery allows the C3 to run during extended or short-term deployments. Each C3 comes with a factory-installed temperature sensor. Optional factory-installed depth sensors and mechanical wipers are also available. The durable delrin housing is highly resistant to harsh environments. Antifouling copper tape pieces are included for placement on the C3 optical head to reduce bio-fouling on and around the sensors. C-Soft Windows™ based software allows for intuitive calibration, datalogging set-up and file management capabilities as well as digital or analog data integration.

Customized Optical Sensors

Choose up to three optical sensors to be factory installed for a variety of applications.

Available Optical Sensors


- Blue Green Algae
 - Phycoerythrin (marine)
 - Phycocyanin (freshwater)
- CDOM/FDOM
- Chlorophyll *in vivo*
- Fluorescent Dye Tracing
 - Fluorescein
 - PTSA
 - Rhodamine
- Hydrocarbons
 - Crude Oil
 - Refined Fuels
- Turbidity
- Wastewater Monitoring
 - Optical Brighteners
 - Tryptophan


Contact us for Custom Optics


Highlights of the C3


- One, Two or Three Optical Sensors
- Temperature Sensor Included
- Optional Depth Sensor
- Optional 3-Brush Mechanical Wiper
- All Plastic Housing
- Robust Memory – Over 64,000 Data Lines!
- Easy to Use Software with Data Management Capabilities
- Optional C-ray Deployment Body Enables Horizontal Towing



 Digital or Analog integration with a CTD profiler or third party platform

 Extended Deployments in the Self-Contained Mode with Submersible Battery

 Reduced Bio-Fouling with Antifouling Copper Tape

 Solid Secondary Standard used to check signal stability or correlate to a primary standard

Reliable Instruments for an Unreliable World



Submersible Fluorometer



Application	Minimum Detection Limit	Dynamic Range	C3 Physical Specifications	
CDOM/FDOM	0.15 ppb** 0.5 ppb***	0-1250 ppb** 0-5000 ppb***	Weight in Air	1.64 kg; 3.6 lbs
Chlorophyll <i>in vivo</i>	0.025 µg/L	0-500 µg/L	Length	23 cm; 9.1 in
Fluorescein Dye	0.01 ppb	0-500 ppb	Diameter	10 cm; 3.9 in
Oil - Crude	0.2 ppb***	0-2700 ppb***	Material	Delrin Plastic
Oil - Fine	10 ppb*	>10,000 ppb*	Temperature	-2 to 50 degrees C.
	10 ppm****	>100ppm****	Depth	0 to 600 meters
Optical Brighteners	0.6 ppb***	0-15,000 ppb***	C3 Electrical Specifications	
Phycocyanin	2 ppb ^{PC}	0-40,000 ppb ^{PC}	Output	Digital (ASCII); Analog (0 - 5 volt)- optional
Phycocerythrin	0.15 ppb ^{PE}	0-750 ppb ^{PE}	Interface	RS232 Interface
PTSA Dye	0.1 ppb***	0-650 ppb***	Minimum Sample Interval	1 Second
Rhodamine Dye	0.01 ppb	0-1000 ppb	Minimum Power Supply	8 - 30 volts; 5 watts
Tryptophan	3 ppb	>20,000 ppb	Maximum Current Draw @ 12 volts	
Turbidity	0.05 NTU	0-3000 NTU	- operational	200 mA
			- sleep mode	3 mA

* 1,5 Naphthalene Disulfonic Disodium Salt
 ** Quinine Sulfate
 *** PTSA (1,3, 6, 8 - Pyrenetetrasulfonic Acid Tetrasodium Salt)
 **** BTEX (Benzene, Toluene, Ethylbenzene, Xylenes)
^{PC} Phycocyanin pigment from Prozyme diluted in Deionized water
^{PE} Phycocerythrin pigment from Prozyme diluted in Deionized water

Ordering Information

INSTRUMENT	PART NUMBER	AVAILABLE FACTORY-INSTALLED OPTICS	PART NUMBER
C3 Submersible Fluorometer	2300-000	Blue Green Algae - Phycocerythrin	2300-230
C3 ACCESSORIES	PART NUMBER	Blue Green Algae - Phycocyanin	2300-231
3-Brush Mechanical Wiper	2300-450	CDOM/FDOM	2300-251
Pressure Sensor	2300-360	Chlorophyll <i>in vivo</i>	2300-200
Antifouling Copper Tape (15)	2300-506	Crude Oil	2300-253
Analog Output Adapter	2300-480	Fluorescein Dye	2300-220
Submersible Battery Pack	2200-601	Optical Brighteners	2300-252
Battery Pack Bracket	2300-603	PTSA Dye	2300-250
Flow Cap	2300-700	Refined Fuels	2300-255
Shade Cap (Recommended for most deployments)	2300-500	Rhodamine Dye	2300-210
Shade Cap Weight	2300-510	Tryptophan	2300-256
C-ray Shade Cap	2300-502	Turbidity	2300-240
C-ray Towed Deployment Body	2300-750	<i>Contact us for Custom Optics</i>	
Solid Secondary Standard	2300-901	OIL SPILL RESPONSE FOR SMART PROTOCOL	PART NUMBER
UV Solid Secondary Standard	2300-902	SMART Firmware	2200-201
0.6 Meter Pigtail Interface Cable w/ Locking Sleeve	2200-170	C-ray Shade Cap	2300-502
Communication and Integration Cable	2300-115	C-ray Deployment Body	2300-750
Boosters (Set of 2)*	2200-900		
10 Meter Extender Cable	105-2595		
25 Meter Extender Cable*	105-2596		
50 Meter Extender Cable*	105-2597		

*Boosters are required for cable lengths greater than 10 meters

Contact Us

Toll-Free : 1.877.316.8049 Email : sales@turnerdesigns.com Address:
 Phone : 408.749.0994 Web : www.turnerdesigns.com 845 West Maude Avenue
 Fax : 408.749.0998 Sunnyvale, CA 94085